

flexFOOD™ Milk 212 (212 MK)



Heavy-duty food grade suction and discharge hose

Crafted to FDA and 3-A nontoxic standards. Ideal for milk hauling (tank truck) and pick-up, offering flexibility, visual clarity, precise flow, and optimal drainability.

FEATURES

The food grade hose is constructed in compliance with FDA and 3-A nontoxic specifications. Clear sidewall permits visual check of material flow. The smooth bore allows for precise flow because no irregularities in the wall can cause interruptions. Smooth bore also promotes drainability.

APPLICATIONS

A more flexible version of our KanaFlo FG hose. The KanaFlo MK hose is designed specifically for milk hauling (tank truck) and pick-up.

CONSTRUCTION


Produced entirely of compounds in compliance with FDA and 3-A nontoxic specifications, flexible PVC, rigid PVC helix, smooth bore, smooth O.D.

TEMP. RANGE

-13°F to 140°F

NOTE

Made with NSF51 approved materials



AVAILABLE SIZES

ID in / mm	OD in / mm	Pitch in / mm	Minimum Bend Radius in / mm	Working Pressure PSI / bar	Vacuum Rating inHg / kPa	Weight lb/ft / kg/m	Standard Length ft / m
1-1/2 / 38.1	1.82 / 46.2	0.30 / 7.6	2.0 / 51	66 / 4.55	29.8 / 100.9	0.44 / 0.65	100 / 30.5
2 / 50.8	2.39 / 60.7	0.33 / 8.4	2.5 / 64	66 / 4.55	29.8 / 100.9	0.74 / 1.1	100 / 30.5
2-1/2 / 63.5	2.93 / 74.4	0.37 / 9.4	4.7 / 119	66 / 4.55	29.8 / 100.9	1.01 / 1.5	100 / 30.5
3 / 76.2	3.43 / 87.1	0.37 / 9.4	6.1 / 155	62 / 4.27	29.8 / 100.9	1.21 / 1.8	100 / 30.5

Over flexing or repeated flexing of hose within 18" of fitting is a common cause of hose failure. Installing a 12"-14" section of our Banding Coil at the end of the hose should be considered. *Kanaflex will not be responsible for damage to hose due to over flexing.*